

MTP/MPO Trunk Cables Datasheet

IDEAL FOR DATA CENTER HIGH DENSITY CABLING SYSTEM

Designed for data center applications requiring quick infrastructure deployment such as main, horizontal, and zone distribution areas.



MTP/MPO Trunk Cables

MTP/MPO trunk multifiber cable assemblies facilitate rapid deployment of high density backbone cabling in data centers and other high fiber environments, reducing network installation or reconfiguration time and cost. They are used to interconnect cassettes, panels or ruggedized MTP/MPO fanouts, spanning MDA, HDA and EDA zones.

Features

- 1.US Conec MTP connector, Senko MPO Plus premium connector
- 2.SMF-28 Ultra optical fiber, Corning Clearcurve OM3/OM4 fiber, YOFC Maxband OM5 fiber
- 3.OS2, OM3, OM4, OM5 available
4. 0.35dB elite low loss connector
- 5.Factory terminated and tested
- 6.Allow easy migration from 10GbE to 40GbE or 100GbE
- 7.Pulling eyes are provided as an option to protect the fiber ends during installation



Technical Specification

Construction	Description
Fiber Count	8-144 Fibers
Fiber Mode	Single mode: OS2 9/125μm Multimode: OM3/OM4/OM5 50/125μm
Fiber Brand	OS2: SMF-28 Ultra optical fiber OM3/ OM4: Corning ClearCurve fiber OM5: YOFC Maxband fiber
Connector Type	MTP Female, Male; MPO Female, Male
Connector Brand	US Conec MTP, Senko MPO Plus
Polarity	Type A, Type B, Type C
Cable Jacket Ratings	Plenum (OFNP) Low Smoke Zero Halogen (LSZH) Riser (PVC)
Cable Type	Bunch

Color Codes	MTP	MPO
Cable Jackets	OS2: Yellow OM3: Aqua OM4: Magenta OM5: Lime Green	OS2: Yellow OM3: Aqua OM4: Magenta OM5: Lime Green
Connectors	OS2: Green OM3/OM4: Aqua OM5: Lime Green	OS2: Green OM3/OM4: Aqua OM5: Lime Green
Boots	8 Fibers: Grey 12 Fibers: Black 24 Fibers: Red	8/12/24 Fibers: Black



Technical Specification

Optical Properties	Description
Attenuation (dB/km)	Single Mode: ≤0.32 at 1310nm, ≤0.18 at 1550nm OM3/OM4 Multimode: ≤2.3 at 850nm, ≤0.6 at 1300nm OM5 multimode: ≤2.3 at 850nm, ≤1.7 at 953nm, ≤0.6 at 1300nm
Insertion Loss (dB)	Single Mode: ≤0.35, Multimode: ≤0.30
Return Loss (dB)	Single Mode: UPC Polish: ≥60, APC Polish: ≥50 Multimode: ≥20
Wavelength (nm)	Single Mode: 1310/1550, Multimode: 850/1300

Transmission Distance

Multimode fiber backbone cabling distances for 10 Gbps, 40 Gbps, and 100 Gbps applications.

Backbone Application	Standard Specified Max. Distance		
	OM3	OM4	OM5
10GBASE-SR (850nm)	300m (984ft)	400m (1312ft)	400m (1312ft)
40GBASE-SR4	100m (328ft)	150m (492ft)	150m (492ft)
40GBiDi	100m (328ft)	150m (492ft)	200m (689ft)
40GBASE-eSR4	300m (984ft)	400m (1312ft)	400m (1312ft)
40G SWDM4	240m (787ft)	350m (1148ft)	440m (1444ft)
100GBASE-SR10	100m (328ft)	150m (492ft)	150m (492ft)
100GBASE-SR4	70m (230ft)	100m (328ft)	100m (328ft)
100GBASE-eSR4	200m (689ft)	300m (984ft)	300m (984ft)
100G SWDM4	75m (246ft)	100m (328ft)	150m (492ft)